


Sight glass fig. 3880 cast iron flange



Characteristics

- Type:** 3880
- Housing material:** Cast iron
- Material quality:** EN-JL1040
- Connection:** Flange
- Pressure rating flange:** PN16
- Material glass:** Soda lime
- Material cover:** EN-JL1040
- Material cover gasket:** Graphite



| DN mm | L mm | E mm | F mm | G mm |
|----------|---------|---------|---------|---------|
| 15 | 130 | 32 | 45 | 10 |
| 20 | 150 | 32 | 45 | 10 |
| 25 | 160 | 48 | 63 | 10 |
| 32 | 180 | 65 | 80 | 12 |
| 40 | 200 | 65 | 80 | 12 |
| 50 | 230 | 80 | 100 | 15 |
| 65 | 290 | 80 | 100 | 15 |
| 80 | 310 | 100 | 125 | 20 |
| 100 | 350 | 125 | 150 | 25 |
| 125 | 400 | 150 | 175 | 25 |
| 150 | 480 | 175 | 200 | 30 |
| 200 | 600 | 175 | 200 | 30 |

| | |
|-------------------------|----------------|
| With borosilicate glass | 16 bar - 280°C |
| With soda-lime glass | 16 bar - 150°C |

| Nominal inner diameter | Pressure rating | Built-in length mm | Type of flow indicator | Article |
|------------------------|-----------------|-----------------------|------------------------|----------|
| DN20 | PN16 | 150 | Driptube | 11813424 |
| DN25 | PN16 | 160 | Driptube | 11813425 |
| DN32 | PN16 | 180 | Driptube | 11813426 |
| DN40 | PN16 | 200 | Driptube | 11813427 |
| DN50 | PN16 | | | 11813428 |
| DN65 | PN16 | 290 | Driptube | 11813429 |
| DN80 | PN16 | 310 | Driptube | 11813430 |
| DN100 | PN16 | 350 | Driptube | 11813431 |

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.