




## Sight glass fig. 3890

### Characteristics

**Type:** 3890

**Connection:** Welded-in

**Pressure rating flange:** PN10



DN	D mm	d1 mm	d2 mm	s mm
25	115	48	63	10
40	150	65	80	12
50	165	80	100	15
80	200	100	125	15
100	220	125	150	20
125	250	150	175	20
150	285	175	200	25
200	340	225	250	30

	Soda-lime glass	Borosilicate glass
Temperature	150 °C	280 °C
Oper. press.	10 bar	10 bar

Nominal inner diameter	Pressure rating	Type of flow indicator	Article
DN40	PN10	Vane	13402104
DN50	PN10		12550818
DN80	PN10		13402109
DN100	PN10	Vane	13402108
DN25	PN10		13402105
DN50	PN10		13401990
DN50	PN10		12550813
DN80	PN10		12357904
DN100	PN10		13402107
DN125	PN10		13402106
DN150	PN10		13401991
DN200	PN10		13401992

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.